

# A8

## APPLICATIONS

- medium to large size touring
- medium to large installations
- music reinforcement with A8SUB subwoofer

## FEATURES

- array depending vertical coverage pattern
- system is configurable from 2 to 24 units
- dedicated rigging hardware
- ground stacking without bumper
- A8SUB hardware compatible with A8



## A8 - SPECIFICATIONS

Frequency Response (-6 dB): 120 Hz – 20 kHz  
 Horizontal Coverage (-6 dB): 100 degrees  
 Vertical Coverage (-6 dB): 10 degrees  
 Max SPL LF: 125/131 dB (free space)  
 Max SPL HF: 135/141 dB (free space)  
 Sensitivity, 1w/1m LF: 102 dB (free space)  
 Sensitivity, 1w/1m HF: 115 dB (free space)  
 Impedance LF/HF: 8 ohms  
 Power handling LF: 200 W cont, 800 W peak  
 Power handling HF: 100 W cont, 400 W peak  
 Crossover: Active, A8 Preset

### Drivers

LF: (1) x 8" neodymium magnet cone driver, 2" voice coil, reflex-tuned waveguide  
 HF: (2) x 1" compression driver, dual entry CD-horn

### Enclosure

Enclosure material: Birch plywood, textured black paint finish  
 Grille: Cold rolled steel grille, textured black paint finish  
 Connectors: (2) x NL4, +/-1: LF, +/-2 HF  
 Dimensions: 690 mm x 248 mm x 270 mm  
 Weight: 20 kg

